

Product datasheet

Specifications



Kaedra - for modular device - 2 x 12 modules - 1+1 terminal blocks

Local distributor code:

391535886

13983

EAN Code: 3303430139836

Main

Range	Mureva
Product name	Mureva Enclosure
Product or component type	Weatherproof enclosure
enclosure type	Enclosure for modular device
Mounting plate description	Slotted

Complementary

Enclosure mounting	Surface
9 mm pitches	24
Number of 18 mm modules per row	12
Total number of 18 mm modules	24
Number of horizontal rows	2
Electrical insulation class	Double insulation Class II
Provided equipment	2 marking kit 2 wiring strap 1 terminal block 32 holes 1 terminal block support
Type of front cover	Transparent Reversible
Power dissipation in W	34 W
[In] rated current	63 A
Type of rail	DIN
Number of pre-cutouts PG ISO	17
Number of terminal blocks	1 earth (screw connection) with 32 outgoing
Distribution block outgoing	16 x 16 mm ² + 16 x 10 mm ²
Locking options description	Optional keylock
Enclosure material	Self-extinguishing polymer
Width	340 mm
Height	460 mm
Depth	160 mm
Internal depth	88 mm
Colour	Door: transparent green Enclosure: light grey (RAL 7035)

Environment

Standards	IEC 60670-1 IEC 60670-24 EN 50262 IEC 60695-2-1
Fire resistance	650 °C conforming to IEC 60695-2-1
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to EN 50102
Environmental characteristics (UV)	UV resistant: class 3 conforming to ISO 4582:2010 Ultraviolet degradation test conforming to ISO 4892-2:2013
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	17.000 cm
Package 1 Width	36.000 cm
Package 1 Length	47.500 cm
Package 1 Weight	3.432 kg
Unit Type of Package 2	P12
Number of Units in Package 2	28
Package 2 Height	118.000 cm
Package 2 Width	80.000 cm
Package 2 Length	120.000 cm
Package 2 Weight	108.000 kg

Logistical informations

Country of origin	IT
--------------------------	----

Contractual warranty

Warranty (in months)	18
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	19 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	16 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Average percentage of recycled plastic content	27 %
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	5305d5d6-3783-4b3d-abd0-61fa4a6023d7
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
Halogen-free status	Halogen free plastic parts product

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	86
End of life manual availability	No need of specific recycling operations
Take-back	No

Technical Illustration

Exploded view

