



Main

Range	EVlink
Product or component type	Charging cable
Accessory / separate part category	Cabling accessory
Network number of phases	Three phase
Poles description	3P + N
[In] rated current	32 A
[Us] rated supply voltage	380...415 V AC 50/60 Hz
Socket number	2

Complementary

Plug type	T2 / silver plated contacts charging station end
Connector type	T2 vehicle end silver plated contacts T2 charging station end silver plated contacts
Range compatibility	EVlink parking EVF1 charging station EVlink parking EVW1 charging station EVlink parking EVF2 charging station EVlink parking EVW2 charging station EVlink Smart Wallbox EVB1 charging station EVlink Wallbox EVH2 charging station
Standards	IEC 62196-2 IEC 62196-1
Product certifications	CE
Length	5 m
Net weight	3.2 kg
Colour	Grey

Environment

IP degree of protection	IP44 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-30...50 °C
Ambient air temperature for storage	-40...80 °C
Relative humidity	5...95 %

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information