

Flush-mounting boxes UP¹ ECON® with ECON® multi-membrane



One-gang box UP¹ ECON®

- Solution for plaster installation
- Side-neutral combination
- Many through-wiring possibilities
- With 4 x 3 screw domes
- Standardised combination distance 71 mm

Article no:	1055-25
EAN:	4013456587304
Depth	46 mm
Screw spacing	60 mm
Number of screw domes	4 x 3
Splayed claw fields	2
Tool-free line and conduit entries up to M25 in the combination range	2
Toolless line and pipe entries up to M25 on the box circumference	4
Toolless cable entries up to Ø 11 mm in the bottom of the box	2
Toolless pipe entries up to M25 in the box bottom	2
Halogen-free	Yes
Air-tight	Yes
Packaging inner/dispatch	25/450

The flush-mounting boxes UP¹ ECON® combine the advantages of the UP¹ programme with certified air tightness. They enable installation in accordance with DIN 18015-5, thus ensuring energy-efficient and safe electrical installation. They offer a wide range of options for air-tight conduit and cable entry.

- Stable and side-neutral combination
- Fully insulated through-wiring close to the base for deep boxes
- Breakaway bridge
- 4 triple screw domes / expanding claw fields for secure hold
- Introductions in the bottom of the box and electric cable and cable feed-throughs near the bottom
- Luftdichte Ausführung mit ECON® Multi-Membran
- Avoids leaks in exterior facades made from hollow chamber blocks
- Variable and tool-free cable and conduit entries
- The product has been tested for harmful substances and can be incorporated into sustainable construction projects using the SHI product passport

