

Cavity wall installation boxes



O-range® one-gang box, Depth 49 mm

- Screws ensure permanent fixing
- 90° conduit entry angle for convenient installation in pipe installations
- Entries can be broken out for cables and conduits
- Integrated cable retention of the NYM cable, self-locking of the conduit
- Fully insulated through-wiring for combinations using support connectors
- Can be combined with all O-range® programme applications

Article no:	9063-02
EAN:	4013456548244
For panel thickness	7 - 40 mm
Depth	49 mm
Cut hole Ø	68 mm
Device screws +/-	2
Ø 20 / 25 mm combination entries	2
Cable entries 3 x 2.5 mm ² or 5 x 1.5 mm ²	2
Cable entries 3 x 1.5 mm ²	2
Cable entries for low voltages	2
Support connectors for each package	7
Packaging inner/dispatch	25/250

The KAISER cavity wall installation boxes with proven mounting lug technology and improved product features. A practical design and a large selection of cable and conduit entries allow a large number of applications. Additional boxes for installation in thinly boarded walls or solid wood walls complete the wide range. VDE certification documents the high level of quality.

- Screws ensure permanent fixing
- Entries can be broken out for cables and conduits
- Combinable and through-wiring by using support connectors
- Fixing of devices by means of pre-mounted device screws

O-range®   