



DK 0400 G

IP66

4 mm²

- Cable junction box for normal environment and protected outdoor
- without terminals
- dimensions H x W x D: 104 x 104 x 70 mm
- with elastic membranes, which can be removed for cable entry via cable glands

ELECTRICAL PROPERTIES

Rated insulation voltage: $U_i = 1000\text{ V}$

CONNECTION DATA

CABLE ENTRIES

Cable entries:

Number of cable en-tries	Type of cable entry	Size of the metric knock-outs	Sealing range of the cable entry	Position of cable entry
7	elastic mem-branes	M20, M25	9 mm - 17 mm	wall
1	elastic mem-branes	without	6 mm - 15 mm	bottom

MECHANICAL PROPERTIES

Type of lid fastening:	Quick locking: opening and closing by quarter turn, locked position well visible (open - locked)
Delivered accessories:	External brackets, retaining strap, sealing plug
IP degree of protection:	IP66
Impact strength:	IK07
Sealable without accessories:	Yes

AMBIENT CONDITIONS

Application area:	Indoor installation
Maximum ambient temperature 24 h:	35 °C
Ambient temperature:	-25 °C up to +40 °C
Relative humidity:	≤ 50 % at 40 °C, ≤ 100 % at 25 °C

MATERIAL PROPERTIES

Material:	Polypropylene
Glow wire test according to IEC 60695-2-11:	750 °C
UL 94:	V-2
Temperature resistance:	-25 °C up to +80 °C
Halogen-free:	Yes
Silicone-free:	Yes

DIMENSIONS

Height:	104 mm
Width:	104 mm
Depth:	70 mm
Net weight:	0.122 kg
Mounting height:	83 mm
Mounting width:	83 mm
Mounting depth:	55 mm

CERTIFICATES

conforming to the standards:	DIN EN 60670-1/-22, IEC 60670-1/-22
Certificates:	

Type of certificate	Certificate number
VDE	40049684

SALES DATA

Product number:	62000002
EAN:	4012591124948
Pack unit:	5
Customs tariff number:	85369010
ETIM class:	DYNAMIC: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-8.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-7.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-6.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-5.0: EC002600 - Box/housing for surface mounting on the wall/ceiling ETIM-4.0: EC002600 - Box/housing for surface mounting on the wall/ceiling

NOTE


When using the sealing plugs supplied, the specified protection class is not changed.


TENDER TEXT

Cable junction boxes according to IEC 60670-22 with removable, elastic sealing membranes. Suitable for indoor rooms and protected outdoor installation according to DIN VDE 0100, part 737. For ambient temperature max. +40 °C and min. -25 °C, with relative humidity 50% at +40 °C or 100% at +25 °C. Material temperature resistance from -25 °C to +70 °C, flammability per VDE 0471, part 2 - glow wire test 750 °C, UL Subject 94 V-2. Degree of protection as per IEC 60529: IP 66. Rated insulation voltage 1000 V. Material: thermoplastic, halogen and silicone free. Colour: grey, RAL 7035. Cover fixation by quick-release, sealable without accessories. Plug-in external brackets for wall mounting are included. Manufacturer: HENSEL ENYCASE DK.


Rated cross-section: 4 mm², dimensions HxWxD 104 x 104 x 70 mm

DRAWINGS





2x Ø9-17 mm



2x Ø9-17 mm 2x Ø9-17 mm
2xM20/25 2xM20/25

