



OTL50 grey 1xAl/Cu 1,5-50mm<sup>2</sup> 1500V  
Universal terminal

MAA1050A10

|                |                         |
|----------------|-------------------------|
| Product code   | MAA1050A10              |
| EAN            | 4744397013811           |
| ETIM Class     | EC000897                |
| Product series | Universal terminals OTL |
| CN8 code       | 85369010                |
| Unit           | pcs                     |
| Package size:  | 48                      |
| Net weight     | 0,03 kg                 |
| Net length     | 0,05 m                  |
| Net width      | 0,018 m                 |
| Net depth      | 0,043 m                 |

|                                                                          |                               |
|--------------------------------------------------------------------------|-------------------------------|
| Connectable conductor cross section fine-strand without cable end sleeve | 1.5 - 35 mm <sup>2</sup>      |
| Connectable conductor cross section fine-strand with cable end sleeve    | 1.5 - 35 mm <sup>2</sup>      |
| Connectable conductor cross section solid-core                           | Unknown                       |
| Connectable conductor cross section multi-wired                          | 1.5 - 50 mm <sup>2</sup>      |
| Rated current I <sub>n</sub>                                             | 160 A                         |
| Rated voltage                                                            | 1500 V                        |
| Type of electrical connection 1                                          | Screw connection              |
| Type of electrical connection 2                                          | Not applicable                |
| Number of levels                                                         | 1                             |
| Number of clamp positions per level                                      | 2                             |
| Mounting method                                                          | DIN rail (top hat rail) 35 mm |
| Material insulation body                                                 | Thermoplastic                 |
| Operating temperature                                                    | -25 - 80 °C                   |
| Inflammability class of insulation material according - to UL94          |                               |
| Width                                                                    | 18 mm                         |
| Height                                                                   | 43 mm                         |
| Depth                                                                    | 50 mm                         |
| Explosion-tested version 'Ex e'                                          | No                            |
| Closing plate required                                                   | No                            |
| Colour                                                                   | Grey                          |
| Internally connected stages                                              | Yes                           |