

ECTG2125



HF RIGID CONDUIT 33421 Ø25 mm - 3 m

Conduits and fittings > Conduits > Rigid conduits > Series tg21
- pp - class 33421 - 750 n > plastic conduits > 3 meters - lenght



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

Technical Symbols/Marks/Approvals

HF	+90°	CE	RoHS II	MADE IN ITALY
----	------	----	---------	---------------

Norms

EN 61386-1 EN 61386-21 IEC 60754-1 IEC 60754-2 EN 61034-2


Etim

GROUP EG000002 - Pipes/hoses for cable installation

CLASS EC001174 - Plastic installation tube

Flush-mounted installation	Yes	Material	Polypropylene (PP)	Halogen free	Yes
Colour	Grey	RAL-number	7035	UV resistant	No
Suitable for underground installation	No	Operating temperature	-25-90 °C	Bending strength	Rigid
Compressive strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	Impact strength class according to EN 61386-1	Medium (class 3 / 2 Joule)	With sleeve	No
Fire retardant version	Yes	Surface mounting	Yes	Suitable for installation on wood	Yes
Suitable for hollow wall installation	Yes	Suitable for concrete installation	Yes	Machine and systems installation	Yes
Suitable for underfloor installation (screed)	Yes	Suitable for outdoor installation	Yes	Inner diameter	20.9 mm
Outer diameter	25 mm	High conducting inner coating	No	With metre indication	No

Documentation available for download



Certification

Test Report Serie TG20-TG21
Halogen Free-pH-HCI_IMQ.pdf

Barcode



8054320284550

Cardboard

60 MT

8.424 [kg]



8057711599059

Pallet

1440 MT

202.176 [kg]