

**EC75632**



**FLEXIBLE BEND PIPE-PIPE IP65 Ø32 mm - GREY - SPEED SYSTEM**

Conduits and fittings > Accessories and fittings > Joints and fittings > Speed system - ip65 fittings > Coupler bend conduit - conduit > Flexible bend (conduits-conduits)



IMMAGINE RAPPRESENTATIVA REPRESENTATIVE IMAGE

**Technical Symbols/Marks/Approvals**

|      |         |          |      |    |         |               |
|------|---------|----------|------|----|---------|---------------|
| IP65 | UL94 V0 | GWT 960° | IK07 | CE | RoHS II | MADE IN ITALY |
|------|---------|----------|------|----|---------|---------------|

**Norms**

EN 61386-1 EN 61386-21

**Etim**

**GROUP EG000002 - Pipes/hoses for cable installation**

**CLASS EC000936 - Bend for installation tubes**

|   |           |  |                            |  |         |
|---|-----------|--|----------------------------|--|---------|
| <b>Material</b>   | Plastic   | <b>Material quality</b>                              | Polyvinyl chloride (PVC)   | <b>Halogen free</b>                      | No      |
| <b>Surface protection</b>                                 | Untreated | <b>Colour</b>  | Grey                       | <b>Model</b>                             | Plug-in |
| <b>Diameter</b>   | 32 mm     | <b>Flexible</b>                                      | Yes                        | <b>UV resistant</b>                      | Yes     |
| <b>Quality of surface coating</b>                         | Uncoated  | <b>Surface polished</b>                              | No                         | <b>Surface brushed</b>                   | No      |
| <b>Compressive strength class according to EN 61386-1</b> | None      | <b>Impact strength class according to EN 61386-1</b> | Medium (class 3 / 2 Joule) | <b>For nominal tube diameter</b>         | 32 mm   |
| <b>With sleeve</b>  | Yes       | <b>Two-part</b>                                      | No                         | <b>With inspection opening and cover</b> | No      |
| <b>Radius</b>   | 320 mm    | <b>Bend angle</b>                                    | 90 °                       |  |         |

**Technical Characteristics**

length 270 mm

## Barcode



8050507872596

**Pack**

20 NR

2 [kg]



8050507872602

**Cardboard**

80 NR

0.605x0.4x0.26 [m]

8 [kg]